

2026 COLLECTION CATALOG



GP-35 HIGH-PRESSURE GAUGE

- Precision copper coil ensures stable and accurate performance.
- Equipped with a proven Bourdon-type mechanism, it ensures reliable accuracy under high pressure.
- Operating temperature range: -5°C to 45°C (23°F-113°F)
- Dual scale display: 400 bar / 5000 PSI for universal readability.

CE APPROVED



GP-700 3-GAUGE CONSOLE

GP-800 DUAL GAUGE CONSOLE

- Integrated 60-meter / 200ft depth gauge and 400 bar / 5000 PSI pressure gauge with dual scale display.
- The GP-700's integrated compass offers precise directional reading even at wide tilt angles, featuring a gunsight-style window for quick, accurate navigation and an adjustable ratchet bezel for easy underwater reference.

CE APPROVED

GP-33 WRIST COMPASS

- Clear, easy-to-read dial with luminous markings for visibility in low-light conditions.
- Gunsight-style top window enables fast and accurate bearing alignment.
- Fully adjustable ratchet bezel for easy setting and reference underwater.



REGULATOR

I R-2000 BALANCED DIAPHRAGM REGULATOR SET



- Environmentally sealed first stage with balanced diaphragm design.
- Pneumatically balanced second stage for effortless breathing at any depth.
- 2 HP & 4 LP ports for multiple hose configurations.
- Lightweight **braided low-pressure hose** for flexibility and comfort.
- Heat sink connection assists cold-water performance.
- Adjustable breathing control knob.
- Chrome-plated components for corrosion resistance and long-term durability.
- **Nitrox compatible up to 40% out of the box.**
- **Intermediate pressure setting @ 9.5-10.0 bar (137-145psi)**
- **Second stage breathing resistance setting @ 1.1-1.3 inch of.**

CE APPROVED

| R-200 DIAPHRAGM BALANCED FIRST STAGE



- Environmentally sealed diaphragm design prevents contamination and enhances longevity.
- TPU end-cap protector safeguards the diaphragm from impact or abrasion.
- 2 High Pressure (HP) and 4 Low Pressure (LP) ports for flexible hose routing.
- Yoke version rated to 230 bar / DIN version rated to 300 bar.
- Chrome-plated exterior finish for superior corrosion resistance.
- **Nitrox compatible up to 40% out of the box.**
- **Intermediate pressure setting @ 9.5-10.0 bar (137-145psi).**

| O-300 PNEUMATICALLY BALANCED OCTOPUS



- High-performance pneumatically balanced mechanism for consistent airflow.
- Adjustable control knob allows customized breathing resistance.
- Heat sink connection helps warm inhaled air for cold-water diving.
- Comfortable silicone mouthpiece minimizes jaw fatigue.
- Lightweight construction with surge deflection front cover and chrome trim.
- The alternate second stage features a fluorescent yellow soft cover paired with a **36-inch yellow braided hose**, making it highly visible and easy to identify underwater.
- **Breathing resistance setting @ 1.1-1.3 inch of.**

DIVE KNIFE

| K-26 SPEARFISHER'S KNIFE

- The 4 mm 420J2 stainless steel blade provides excellent corrosion resistance and durability.
- The double-edged blade has one smooth edge and one serrated edge with a barb, allowing for versatile use — from cutting rope to precisely handling catch underwater.
- Suitable for divers, freedivers, and spearfishing enthusiasts.



	DIMENSION
Blade length	Approx. 13 cm (5.1")
Overall length	Approx. 25 cm (9.8")
Total weight (with sheath and straps) 240 g (0.53 lb)	

| K-27 SQUEEZE-LOCK DIVE KNIFE



- The knife's squeeze-lock handle allows quick, one-handed release or secure locking, ensuring safe and reliable use.
- The 4 mm 420J2 stainless steel blade provides excellent corrosion resistance and durability.

	DIMENSION
Blade length	Approx. 12.6 cm (5")
Overall length	Approx. 25.2 cm (9.9")
Total weight (with sheath and straps)	241 g (0.53 lb)

| K-60 COMPACT DIVE KNIFE

- The 4 mm 420J2 stainless steel blade provides excellent corrosion resistance and durability.
- Includes a BC hose-mount adapter, allowing the knife to be conveniently attached to a low-pressure inflator hose for easy access during dives.



	DIMENSION
Blade length	Approx. 9.2 cm (3.62")
Overall length	Approx. 19.7 cm (7.8")
Total weight	96g (0.21 lb)



IST SPORTS CORP.

www.istsports.com | diving@istsports.com



PRINTED IN TAIWAN